

Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 13

TECHNOMELT PUR 270/3 G 12KG

SDS No. : 108587
V004.3

Revision: 30.05.2015

printing date: 25.03.2019

Replaces version from: 14.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TECHNOMELT PUR 270/3 G 12KG

Contains:

4,4'-methylenediphenyl diisocyanate
o-(p-Isocyanatobenzyl)phenyl isocyanate

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Assembly and laminating adhesive for general, woodworking and footwear industry

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

Fax-no.: +49 211 798 2009

ua-productsafety.de@henkel.com

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Respiratory sensitizer	Category 1
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Carcinogenicity	Category 2
H351 Suspected of causing cancer.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:	Danger
Hazard statement:	H317 May cause an allergic skin reaction. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H351 Suspected of causing cancer.
Precautionary statement:	P261 Avoid breathing fume.
Prevention	P280 Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statement:	P308+P313 IF exposed or concerned: Get medical advice/attention.
Response	

2.3. Other hazards

Persons suffering from allergic reactions to isocyanates should avoid contact with the product.

SECTION 3: Composition/information on ingredients
3.2. Mixtures**General chemical description:**

1-Component PU adhesive

Base substances of preparation:

Polyurethane prepolymer with isocyanate groups

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
4,4'- methylenediphenyl diisocyanate 101-68-8	202-966-0 01-2119457014-47	1- 3 %	Carc. 2 H351 Acute Tox. 4; Inhalation H332 STOT RE 2 H373 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315 Resp. Sens. 1 H334 Skin Sens. 1 H317
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	227-534-9 01-2119480143-45	< 1 %	Skin Sens. 1 H317 Resp. Sens. 1 H334 Carc. 2 H351 Acute Tox. 4; Inhalation H332 STOT RE 2 H373 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

Inhalation:

Fresh air, oxygen supply, warmth; seek specialist medical attention.

Delayed effects possible after inhalation.

Skin contact:

Molten product. After skin contact cool down immediately with cold water. Do not remove adherent product. Seek medical advice.

Eye contact:

After contact with the hot melt: cool with water, seek medical attention.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

Suspected of causing cancer

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Avoid contact with skin and eyes.

Keep unprotected persons away.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Allow to solidify.

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Hygiene measures:

- Do not eat, drink or smoke while working.
- Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container protected against moisture.
Ensure good ventilation/extraction.
Store in a cool place in closed original container.

7.3. Specific end use(s)

Assembly and laminating adhesive for general, woodworking and footwear industry

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
4,4'-Methylenediphenyl diisocyanate 101-68-8			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
4,4'-Methylenediphenyl diisocyanate 101-68-8		0,05	Exposure limit(s):	=2= If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
4,4'-Methylenediphenyl diisocyanate 101-68-8			STEL (Short Term Exposure Limit) factor:	1 Substance listed with both Peak factor and STEL factor. The Peak factor is supplied with the AGW values.	TRGS 900
4,4'-Methylenediphenyl diisocyanate 101-68-8			Skin designation:	Can be absorbed through the skin.	TRGS 900
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1		0,05	Exposure limit(s):	=2= 1 Substance listed with both Peak factor and STEL factor. The Peak factor is supplied with the AGW values.	TRGS 900
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1			STEL (Short Term Exposure Limit) factor:	1 Substance listed with both Peak factor and STEL factor. The Peak factor is supplied with the AGW values.	TRGS 900
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
4,4'-methylenediphenyl diisocyanate 101-68-8	aqua (freshwater)					1 mg/L	
4,4'-methylenediphenyl diisocyanate 101-68-8	aqua (marine water)					0,1 mg/L	
4,4'-methylenediphenyl diisocyanate 101-68-8	soil				1 mg/kg		
4,4'-methylenediphenyl diisocyanate 101-68-8	STP					1 mg/L	
4,4'-methylenediphenyl diisocyanate 101-68-8	aqua (intermittent releases)					10 mg/L	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	aqua (freshwater)					> 1 mg/L	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	aqua (marine water)					> 0,1 mg/L	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	soil				1 mg/kg		
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	STP					> 1 mg/L	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	aqua (intermittent releases)					10 mg/L	

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
4,4'- methylenediphenyl diisocyanate 101-68-8	Workers	Dermal	Acute/short term exposure - systemic effects		50 mg/kg bw/day	
4,4'- methylenediphenyl diisocyanate 101-68-8	Workers	Inhalation	Acute/short term exposure - systemic effects		0,1 mg/m3	
4,4'- methylenediphenyl diisocyanate 101-68-8	Workers	Dermal	Acute/short term exposure - local effects		28,7 mg/cm2	
4,4'- methylenediphenyl diisocyanate 101-68-8	Workers	Inhalation	Acute/short term exposure - local effects		0,1 mg/m3	
4,4'- methylenediphenyl diisocyanate 101-68-8	Workers	Inhalation	Long term exposure - systemic effects		0,05 mg/m3	
4,4'- methylenediphenyl diisocyanate 101-68-8	Workers	Inhalation	Long term exposure - local effects		0,05 mg/m3	
4,4'- methylenediphenyl diisocyanate 101-68-8	general population	Dermal	Acute/short term exposure - systemic effects		25 mg/kg bw/day	
4,4'- methylenediphenyl diisocyanate 101-68-8	general population	Inhalation	Acute/short term exposure - systemic effects		0,05 mg/m3	
4,4'- methylenediphenyl diisocyanate 101-68-8	general population	oral	Acute/short term exposure - systemic effects		20 mg/kg bw/day	
4,4'- methylenediphenyl diisocyanate 101-68-8	general population	Dermal	Acute/short term exposure - local effects		17,2 mg/cm2	
4,4'- methylenediphenyl diisocyanate 101-68-8	general population	Inhalation	Acute/short term exposure - local effects		0,05 mg/m3	
4,4'- methylenediphenyl diisocyanate 101-68-8	general population	Inhalation	Long term exposure - systemic effects		0,025 mg/m3	
4,4'- methylenediphenyl diisocyanate 101-68-8	general population	Inhalation	Long term exposure - local effects		0,025 mg/m3	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Workers	Dermal	Acute/short term exposure - systemic effects		50 mg/kg bw/day	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Workers	Inhalation	Acute/short term exposure - systemic effects		0,1 mg/m3	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Workers	Dermal	Acute/short term exposure - local effects		28,7 mg/cm2	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Workers	Inhalation	Acute/short term exposure - local effects		0,1 mg/m3	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Workers	Inhalation	Long term exposure - systemic effects		0,05 mg/m3	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Workers	Inhalation	Long term exposure - local effects		0,05 mg/m3	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	general population	Dermal	Acute/short term exposure - systemic effects		25 mg/kg bw/day	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	general population	Inhalation	Acute/short term exposure - systemic effects		0,05 mg/m3	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	general population	oral	Acute/short term exposure - systemic effects		20 mg/kg bw/day	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	general population	Dermal	Acute/short term exposure - local effects		17,2 mg/cm2	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	general population	Inhalation	Acute/short term exposure - local		0,05 mg/m3	

			effects			
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	general population	Inhalation	Long term exposure - systemic effects		0,025 mg/m3	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	general population	Inhalation	Long term exposure - local effects		0,025 mg/m3	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
4,4'-Methylenediphenyl diisocyanate 101-68-8	4,4-Diaminodiphenylmethane	Creatinine in urine	Sampling time: End of shift.	10 µg/g	DE BAT	BAT values reflect the total physical load of workplace substances absorbed through inhalation, dermally, etc. With occupational exposure to MDI, parameter 4,4'-Diaminodiphenylmethane (MDA) in the urine covers all components of a complex MDI mixture, since both monomers and oligomers of the MDI are degraded independent of the exposure path of the monomeric MDI. In contrast, the MAK value for MDI takes into account only the monomer MDI portion.	

8.2. Exposure controls:

Engineering controls:

Use only in well ventilated areas.

Draw off vapors and fumes directly at the point of generation or release. In the case of regular work use bench-mounted extraction equipment.

Respiratory protection:

In case of dust formation, we recommend wearing of appropriate respiratory protection equipment with particle filter P. This recommendation should be matched to local conditions.

Hand protection:

Wear refractive gloves while working with the hot melt.

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.

Skin protection:

Wear protective equipment.

Protective clothing that covers arms and legs.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	solid material solid Whitish
Odor	typical
Odour threshold	No data available / Not applicable
pH	Not applicable
Initial boiling point	No data available / Not applicable
Flash point	; no method No flash point up to 200 °C
Decomposition temperature	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Density	1,25 - 1,35 g/cm ³
(20 °C (68 °F))	
Bulk density	No data available / Not applicable
Viscosity	40.000 - 85.000 mPa.s
(Brookfield; 150 °C (302 °F); speed of rotation: 5 min ⁻¹ ; Spindle No: 28; Conc.: 100 % product)	
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative)	Insoluble
(20 °C (68 °F); Solvent: Water)	
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

Softening point/range	58 - 62 °C (136.4 - 143.6 °F)
-----------------------	-------------------------------

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reaction with water, alcohols, amines.

Reacts with water: Pressure built up in closed vessel (CO₂).

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Humidity

10.5. Incompatible materials

See section reactivity

10.6. Hazardous decomposition products

At higher temperatures isocyanate may be released.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****General toxicological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Persons suffering from allergic reactions to isocyanates should avoid contact with the product.

Sensitizing:

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carcinogenicity:

Suspected of causing cancer

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
4,4'-methylenediphenyl diisocyanate 101-68-8	LD50	> 2.000 mg/kg	oral		rat	EU Method B.1 (Acute Toxicity (Oral))
o-(p- Isocyanatobenzyl)phenyl isocyanate 5873-54-1	LD50	> 2.000 mg/kg	oral		rat	

Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
4,4'-methylenediphenyl diisocyanate 101-68-8	LC50	> 2,24 mg/l	Aerosol		rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
4,4'-methylenediphenyl diisocyanate 101-68-8	LD50	> 9.400 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
o-(p- Isocyanatobenzyl)phenyl isocyanate 5873-54-1	LD50	> 9.400 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
4,4'- methylenediphenyl diisocyanate 101-68-8	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
4,4'- methylenediphenyl diisocyanate 101-68-8	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
4,4'- methylenediphenyl diisocyanate 101-68-8	sensitising	in vivo	guinea pig	

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
4,4'- methylenediphenyl diisocyanate 101-68-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)

Carcinogenicity:

Hazardous components CAS-No.	Result	Species	Sex	Exposure time Frequency of treatment	Route of application	Method
4,4'- methylenediphenyl diisocyanate 101-68-8	carcinogenic	rat	male/female	2 y 6 h/d	inhalation: aerosol	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
4,4'- methylenediphenyl diisocyanate 101-68-8		inhalation: aerosol	main: 2 y; satellite: 1 y 6 h/d; 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
o-(p- Isocyanatobenzyl)phenyl isocyanate 5873-54-1		inhalation: aerosol	main: 2 y; satellite: 1 y 6 h/d; 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

SECTION 12: Ecological information**General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.
Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
4,4'- methylenediphenyl diisocyanate 101-68-8	LC0	> 3.000 mg/l	Fish	96 h	Oryzias latipes	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	EC50	129,7 mg/l	Daphnia	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	EC50	> 1.640 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'- methylenediphenyl diisocyanate 101-68-8	NOEC	> 10 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	LC50	> 1.000 mg/l	Fish	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)

12.2. Persistence and degradability

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
4,4'- methylenediphenyl diisocyanate 101-68-8		aerobic	0 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
4,4'- methylenediphenyl diisocyanate 101-68-8	5,22	92 - 200	28 d	Cyprinus carpio		OECD Guideline 305 E (Bioaccumulation: Flow- through Fish Test)
4,4'- methylenediphenyl diisocyanate 101-68-8						
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	5,22					

12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
4,4'- methylenediphenyl diisocyanate 101-68-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

08 04 09 Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

- 14.1. UN number**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packaging group**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**
not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content 0 %
(VOCV 814.018 VOC regulation
CH)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: 1, slightly water-endangering product. (German VwVwS of July 27, 2005)
Classification in conformity with the calculation method

BG regulations, rules, infos: BG data sheet: BGI 524 Hazardous substances: polyurethane production
and processing / isocyanates (M 044)

Storage class according to TRGS 510: 11

General remarks (DE): This product is in scope of the German regulation
"Chemikalien Verbots Verordnung"

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.