

Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 10

SDS No.: 107005 V003.0

Revision: 10.07.2018

printing date: 25.03.2019

Replaces version from: 31.07.2015

TECHNOMELT PRIMER 183/1 10KG

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TECHNOMELT PRIMER 183/1 10KG

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Wood adhesive / additional products

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0 Fax-no.: +49 211 798 2009

ua-productsafety.de@henkel.com

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information EUH210 Safety data sheet available on request.

Contains Isothiazolinone mixture 3:1 (CIT/MIT). May produce an allergic reaction.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Plastic dispersion, water-based

Base substances of preparation:

Acrylate copolymer dispersion

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
Isothiazolinone mixture 3:1 (CIT/MIT)		0,0001-< 0,0015	Acute Tox. 2
55965-84-9		%	H330
		(1 ppm- < 15 ppm)	Acute Tox. 3
			H301
			Acute Tox. 2
			H310
			Skin Corr. 1B
			H314
			Skin Sens. 1A
			H317
			Aquatic Acute 1
			H400
			Aquatic Chronic 1
			H410
			M factor (Acute Aquat Tox): 100 M factor
			(Chron Aquat Tox): 10

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing. If necessary, see a dermatologist.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

An allergic reaction cannot be excluded after repeated skin contact.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Store in a cool, frost-free place.

Close the container carefully after use and store it at a good ventilated place.

7.3. Specific end use(s)

Wood adhesive / additional products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Germany

None

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Polychloroprene (CR; >= 1 mm thickness) or natural rubber (NR; >=1 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Polychloroprene (CR; >= 1 mm thickness) or natural rubber (NR; >=1 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Protective goggles

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway).

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance dispersion

liquid white

Odor typical

Odour threshold No data available / Not applicable

pH 8 - 9,2

(20 °C (68 °F))

Melting point

No data available / Not applicable

Solidification temperature

No data available / Not applicable

Initial boiling point 100 °C (212 °F)

Flash point No flash point up to 100°C. Aqueous preparation.

Evaporation rate No data available / Not applicable No data available / Not applicable Flammability **Explosive limits** No data available / Not applicable No data available / Not applicable Vapour pressure Relative vapour density: No data available / Not applicable No data available / Not applicable Density Bulk density No data available / Not applicable Solubility No data available / Not applicable

Solubility (qualitative) Miscible

(20 °C (68 °F); Solvent: Water)

Partition coefficient: n-octanol/water

Auto-ignition temperature

No data available / Not applicable

No data available / Not applicable

No data available / Not applicable

Viscosity 15 - 20 mPa.s

(Brookfield; Instrument: RVT; 20 °C (68 °F); speed of rotation: 20 min-1; Spindle No: 1)

Viscosity (kinematic)

Explosive properties

Oxidising properties

No data available / Not applicable
No data available / Not applicable
No data available / Not applicable

Solid content 29 %

9.2. Other information

Flow cup viscosity 21 - 25 s

(20 °C (68 °F); Type of cup: Ford-Cup; Nozzle: 3 mm ;; Dorus-method 548; viscosity Ford-cup)

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information

General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Isothiazolinone mixture 3:1 (CIT/MIT)	LD50	53 mg/kg	rat	not specified
55965-84-9				

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Isothiazolinone mixture	LD50	87,12 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
3:1 (CIT/MIT)				
55965-84-9				

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type		_	time		
Isothiazolinone mixture	LC50	0,171 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
3:1 (CIT/MIT)						Inhalation Toxicity)
55965-84-9						-

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Isothiazolinone mixture 3:1 (CIT/MIT)	corrosive			not specified
55965-84-9				

Serious eye damage/irritation:

No data available.

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Test type	Species	Method
CAS-No.				
Isothiazolinone mixture	Sensitizing		guinea pig	not specified
3:1 (CIT/MIT)	_			_
55965-84-9				

CAS-No.			
Isothiazolinone mixture	Sensitizing	guinea pig	not specified
3:1 (CIT/MIT)			_
55965-84-9			
00,00 0.7			

Germ cell	mutagenicity:
-----------	---------------

No data available.

Carcinogenicity

No data available.

Reproductive toxicity:

No data available.

STOT-single exposure:

No data available.

STOT-repeated exposure::

No data available.

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LC50	0,22 mg/l	96 h	, ,	OECD Guideline 203 (Fish, Acute Toxicity Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,098 mg/l	28 d		OECD Guideline 210 (fish early lite stage toxicity test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Isothiazolinone mixture 3:1	EC50	0,12 mg/l	48 h	Daphnia magna	OECD Guideline 202
(CIT/MIT)					(Daphnia sp. Acute
55965-84-9					Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_		
Isothiazolinone mixture 3:1	NOEC	0,0036 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
(CIT/MIT)		_			magna, Reproduction Test)
55965-84-9					

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	EC50	0,0052 mg/l	48 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,00064 mg/l	48 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Isothiazolinone mixture 3:1	EC20	0,97 mg/l	3 h	activated sludge	OECD Guideline 209
(CIT/MIT)					(Activated Sludge,
55965-84-9					Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances	Result	Test type	Degradability	Exposure	Method
CAS-No.				time	
Isothiazolinone mixture 3:1	inherently biodegradable	aerobic	100 %	28 d	OECD Guideline 302 B (Inherent
(CIT/MIT)					biodegradability: Zahn-
55965-84-9					Wellens/EMPA Test)
Isothiazolinone mixture 3:1	readily biodegradable	aerobic	> 60 %	28 d	OECD Guideline 301 D (Ready
(CIT/MIT)					Biodegradability: Closed Bottle
55965-84-9					Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Isothiazolinone mixture 3:1	3,6			calculation	QSAR (Quantitative Structure
(CIT/MIT)					Activity Relationship)
55965-84-9					

12.4. Mobility in soil

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
Isothiazolinone mixture 3:1	-0,71 - 0,75	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
(CIT/MIT)			Method)
55965-84-9			

12.5. Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or vPvB.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09.

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content 0 %

(VOCV 814.018 VOC regulation

CH)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: 1, slightly water-endangering product. (German VwVwS of July 27, 2005)

Classification in conformity with the calculation method

WGK: WGK = 1, slightly water endangering mixture. Classification according to the

mixture rules in German AwSV regulation annex 1, number 5.2 from 18. April

2017.

Storage class according to TRGS 510: 10

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H301 Toxic if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.